

# Mr Plant Hire plc



SLIPS INTO LIFTS...



...AND IN AND OUT...



...OF INTERNAL DOORS...



EASY OPERATION, NO FORMAL TRAINING NEEDED...



...LIGHTWEIGHT, COMPACT AND EASY TO TRANSPORT

## INDOOR POP-UP GOES ANYWHERE, EVEN THROUGH SINGLE DOORS.

POP-UP replaces the need for ladders and steps to be used indoors in low level access environments.

Its detailed design means that it can offer a multitude of special features that ensure the user has a safe yet simple solution to low level access.

### Key features and benefits

- **Immediate low level access** - 8 seconds to reach full platform height
- **Safe** - designed to be fully stable with a safe working load of 240 kgs
- **Platform height** - fully extended platform height of 1.63 mtrs gives an average working height of 3.63 mtrs
- **Easy to transport** - compact size and weight means it fits onto a small flat back vehicle and can be delivered by a single person
- **Easy to manoeuvre** - 'smooth roll' castors system fitted means it can be positioned by a single operative
- **Easy to operate** - simple hand set controls all elevation/de-elevation functions
- **Training** - no formal training required to operate the POP-UP
- **Affordable** - very competitively priced (offers good price comparison to other low level access equipment solutions)
- **Battery powered with universal charger** - low usage and ownership costs
- **Over 300 operations on one battery charge** - can accommodate heavy 'daily' usage requirements.

# 020 8351 3434



[www.mrplanthire.co.uk](http://www.mrplanthire.co.uk)  
Email: [info@mrplanthire.co.uk](mailto:info@mrplanthire.co.uk)

# Mr Plant Hire plc

## Product Specification

POP-UP has been designed, manufactured and tested in accordance with both the European Standard EN280 and the safety requirements of the European Machinery Directive 98137/EC.

### Load

Safe working load (SWL)	240 kg
Equivalent to	1 person + 160 kg tools and materials

### Dimensions

Maximum platform height	1.63 metres
Maximum working height	3.63 metres
Platform length	1.01 metres
Platform width	0.52 metres
Platform guard rail height	1.10 metres
Toe board height	0.15 metres
Toe board height (gate end)	0.10 metres
Maximum allowable manual force	200 Newtons
Maximum allowable wind speed	0 metres/sec
Maximum allowable chassis inclination	0 degrees

### Electrical system

Voltage	12 volt DC
Motor	0.7 kW
Battery	80Ah
Battery charger	Automatic multi-voltage

### Hydraulic system

Maximum pressure	250 bar
Reservoir capacity	1 litre

### Function speeds (approx.)

Raise	8 seconds
Lower	8 seconds
Approx number of lifts	300 (fully charged with SWL)

### Stowed dimensions

Overall length	1.135 metres
Overall height	1,636 metres
Overall width	0.700 metres

### Weight

Overall mass (GVW)	215kg
Maximum wheel load	350kg



## For all your Access Requirements

**ALUMINIUM TOWERS**  
Double and narrow width, platform heights from 1.5 to 12 metres



**SCISSOR LIFTS**  
6,4 metres to 21 metres



**BOOM LIFT**  
Up to 27 metres

### Training & site surveys

- Free site surveys available
- Aluminium tower training
- Powered access training



120 Hertford Road, Enfield, Middlesex EN3 5AX

Tel: 020 8351 3434 Fax: 020 8805 2423

Email: [info@mrplanthire.co.uk](mailto:info@mrplanthire.co.uk)

[www.mrplanthire.co.uk](http://www.mrplanthire.co.uk)